



Parrett Windows & Doors

Quality Crafted Specialty Windows & Doors

RESIDENTIAL • HISTORIC • CHURCH • COMMERCIAL

Single Hung Window Specs

1. Type:
 - a. Rectangular single hung.
 - b. Rectangular single hung with half circle top.
 - c. Rectangular single hung with arch top.
 - d. Rectangular single hung with gothic top.
 - e. Rectangular single hung with quarter circle top.
 - f. Custom as indicated on the Drawings.
2. Grilles:
 - a. True divided lite type.
 - b. Simulated divided type.
 - 1) Aluminum.
 - 2) Wood.
 - 3) Cellular.
 - 4) With internal glass spacer.
 - 5) Without internal glass spacer.
 - c. Removable wood type.
 - d. Removable cellular type.
 - e. Aluminum between the glass type.
3. Size and Frame Depth: As indicated on the Drawings.
4. Screens:
 - a. Screen Mesh: 18 by 16 charcoal colored fiberglass mesh.
 - b. Screen Mesh: Aluminum.
 - 1) Charcoal.
 - 2) Mill.
 - 3) Brite Bronze.
 - 4) Custom: As indicated on the Drawings.
 - c. Screen Frame:
 - 1) Aluminum, with corners mitered and secured with corner locks; spring-loaded. Color as follows:
 - a) Bronze.
 - b) White.
 - c) Bright Brass
 - d) Custom as indicated on the Drawings.
 - 2) Wood with corners mitered and secured. Finish as follows:
 - a) Natural
 - b) Primed
 - c) Painted
 - d) Stained
5. Hardware and Weatherstripping:
 - a. Jamb Liners:
 - 1) Jamb Liner Inserts: Exterior and interior inserts of vinyl; color as selected from manufacturer's standard colors.
 - 2) Jamb Liner Inserts: Wood interior inserts; finished to match interior frame.
 - 3) Jamb Liner Inserts: None, units to have weight and chain assembly.
 - b. Weatherstripping:

- 1) Compression bulb type at bottom of sash, head jamb, at check rail, and on side jambs.
 - 2) Custom as indicated on the Drawings.
 - c. Locks:
 - 1) Lever arm latch
 - 2) Custom as indicated on the Drawings.
 - d. Balances:
 - 1) Factory installed, concealed in jambs; spring steel coil assemblies as appropriate for sash weight.
 - 2) Factory installed, concealed in jambs; spiral balance assemblies as appropriate for sash weight.
 - 3) Factory installed, weight and chain assemblies as appropriate for sash weight.
 - e. Sash Lifts:
 - 1) High-pressure zinc die cast; two lifts on sash.
 - 2) Custom as indicated on the Drawings.
 - f. Pivot Locking: Lower venting sash provided with mechanisms that permit sash to be tilted 90 degrees inward from bottom pivot and positively held in place for washing.
6. Hardware Finishes:
- a. Window Hardware Exposed to View on Interior when window is closed. Finish in color selected from manufacturer's standard selection as follows:
 - 1) White.
 - 2) Brass.
 - 3) Bronze.
 - 4) Champagne.
 - 5) Custom as indicated on the Drawings.

Double Hung Window Specs

- B. Double Hung Windows:
1. Type:
 - a. Rectangular double hung.
 - b. Rectangular double hung with half circle top.
 - c. Rectangular double hung with arch top.
 - d. Rectangular double hung with gothic top.
 - e. Rectangular double hung with quarter circle top.
 - f. Custom as indicated on the Drawings.
 2. Grilles:
 - a. True divided lite type.
 - b. Simulated divided type.
 - 1) Aluminum.
 - 2) Wood.
 - 3) Cellular.
 - 4) With internal glass spacer.
 - 5) Without internal glass spacer.
 - c. Removable wood type.
 - d. Removable cellular type.
 - e. Aluminum between the glass type.
 3. Size and Frame Depth: As indicated on the Drawings.
 4. Screens:
 - a. Screen Mesh: 18 by 16 charcoal colored fiberglass mesh.
 - b. Screen Mesh: Aluminum.
 - 1) Charcoal.
 - 2) Mill.

- 3) Brite Bronze.
- 4) Custom: As indicated on the Drawings.
- c. Screen Frame:
 - 1) Aluminum, with corners mitered and secured with corner locks; spring-loaded. Color as follows:
 - a) Bronze.
 - b) White.
 - c) Bright Brass
 - d) Custom as indicated on the Drawings.
 - 2) Wood with corners mitered and secured. Finish as follows:
 - a) Natural
 - b) Primed
 - c) Painted
 - d) Stained
5. Hardware and Weatherstripping:
 - a. Jamb Liners:
 - 1) Jamb Liner Inserts: Wood veneer-wrapped interior inserts; finished to match interior frame.
 - 2) Jamb Liner Inserts: None, units to have weight and chain assembly.
 - b. Weatherstripping:
 - 1) Compression bulb type at bottom of sash, head jamb, at check rail, and on side jambs.
 - 2) Custom as indicated on the Drawings.
 - c. Locks:
 - 1) Lever arm latch
 - 2) Custom as indicated on the Drawings.
 - d. Balances:
 - 1) Factory installed, concealed in jambs; spiral balance assemblies as appropriate for sash weight.
 - 2) Factory installed, weight and chain assemblies as appropriate for sash weight.
 - e. Sash Lifts:
 - 1) High-pressure zinc die cast; two lifts on sash.
 - 2) Custom as indicated on the Drawings.
6. Hardware Finishes:
 - a. Window Hardware Exposed to View on Interior when window is closed. Finish in color selected from manufacturer's standard selection as follows:
 - 1) White.
 - 2) Brass.
 - 3) Bronze.
 - 4) Black.
 - 5) Champagne.
 - 6) Custom as indicated on the Drawings.