


HUNG WINDOWS (Weight & Chain)



Parrett Windows & Doors

*Durability, True Quality, & Simply Beautiful
"Experience the Difference"*

RESIDENTIAL • HISTORIC • CHURCH • COMMERCIAL

Phone: 1-800-541-9527 info@parrettwindows.com
Fax: 1-877-238-2452 www.parrettwindows.com

Date: _____ Company: _____ Email: _____ Order:
Parrett Attn: _____ From: _____ Original Quote #: _____
Quote:
of Pages: _____ Phone: _____ P.O. #: _____
RE: _____ Fax: _____ Job Name: _____

Hung Window Type & Configuration

Aluminum Clad

Single Hung Double Hung Triple Hung

- 2-1/4" Sash Thickness
- 6-9/16" Minimum Jamb Depth for SH & DH Units
- 9.75" Jamb for Triple Hungs

*Double hungs have spiral balance top sash operation

Weight Type:

- Steel (standard)
 Stackable

Chain/Rope

- Chain (standard)
 Nylon Rope

Child Safety Sash Limiter:

- Yes No

All Wood

Single Hung Double Hung Triple Hung

Standard

- 1-3/4" Sash Thickness
5-1/2" Min Jamb Depth (SH&DH)
• 7-7/8" Jamb for Triple Hungs
• Std. recommended for frame sizes up to approx. 42" X 84"

Magnum

- 2-1/4" Sash Thickness
6-9/16" Min Jamb Depth (SH/DH)
• 9-1/2" Jamb for Triple Hungs
• Mag. recommended for frame sizes over approx. 42" X 84"

Weight Type:

- Steel (standard)
 Stackable

Chain/Rope

- Chain (standard)
 Nylon Rope

Window Wash Bolts (Steel):

- Yes No

Child Safety Sash Limiter:

- Yes No

Wood Species

Accoya
Alder
Appalacian Cherry
Birch
Black Walnut
Cypress
Douglas Fir
Hard White Maple
Hickory
Knotty Alder
Knotty Pine
Mahogany
Sapele
South American
African
Pine
Poplar
Western Hemlock
Western Red Cedar
White Oak
Other _____

Is FSC Certified Lumber Required?
Yes No

Glass Specification

Single Pane Clear
Insulated Clear
Insulated Low E
RLE 71-38
Low E 272
Other: _____
Laminated STC Rating: _____
Insul. Hurricane Impact
Spandrel Glass
Vintage/Restoration Glass
Decorative Glass
Caming Color:
Zinc/Brushed Nickel
Brass
Black Patina
Antique Patina
Other _____

Glass Strength

Annealed
Tempered
Laminated

Other Glass Options

Glass Tint
Bronze
Green
Grey
Obscure
Frosted
Gluechip
Pattern 516 Spraylite
Other _____

Spacer Bar
Mill Finish
Stainless Steel
Bronze
Black
Warm Edge
Other _____

Grille Type

Aluminum Grille in Airspace
5/8" Flat Bar
11/16" Sculptured Bar
15/16" Sculptured Bar
Color(s): _____
Wood Interior Grille
Grille Profile #: _____
Surround No Surround
Simulated Divided Lite
Int. Profile #: _____
Ext. Profile #: _____
W/Spacer Bar No Int. Spacer
Black Tape Gray Tape

True Divided Lite

Int. Profile #: _____
Ext. Profile #: _____

Grille Pattern

of Rectangle Lites: _____
of Radius Lites: _____
of Gothic Lites: _____
of Diamond Lites: _____

Casing & Trim

Exterior
None
Flat Casing, Width: _____
Brickmould Profile: _____

Interior

None
Flat Casing, Width: _____
Trim Profile: _____

Window Finishing

Aluminum Clad: AAMA 2603 Paint
AAMA 2605 Kynar
Anodized
Wood Grain Paint
OR
Exterior Wood: Unfinished
Painted
Ultra Primed
Stain & Clear Coat
Color: _____
Interior Wood: Unfinished
Painted
Ultra Primed
Stain & Clear Coat
Color: _____

Hardware Finish

Unlacquered Brass
Lacquered Brass
Oil Rubbed Bronze
Satin Nickel
Polished Chrome
Painted White
Other: _____

**custom plated/painted finishes are available*

Locks & Lifts

Sash Locks
Phelps LKF14 (std)
Phelps LKF18
Phelps LKF281/381
No Locks
Other": _____
Sash Lifts
Phelps LF23 (std)
Phelps LFM26
Phelps LFD30
Phelps LFD31
No Lifts
Other": _____

Screen Information

Frame Options
Alum Fixed Screen
Wood Fixed Screen
Rolldown Screen
No Screen

Mesh Options
Fiberglass
High Transpar.
Brass/Bronze
Aluminum

Unit Size:

Jamb to Jamb Brickmould to Brickmould
Rough Opening Masonry Opening

Jamb Depth:

see mininum jamb depths above

Drawings/Sketches

FOR BEST RESULTS,SAVE THIS PDF TO YOUR DEVICE AND THEN OPEN IT IN ADOBE READER, ENTER INFORMATION, THEN CLICK SUBMIT VIA E-MAIL (SOME INTERNET BROWSERS DO NOT SUPPORT FORM FUNCTIONS)

Notes