

Parrett

Windows & Doors

WINDOW SHOWCASE VOL. 5

Piston Operated Awning

- MULTIPOINT LOCKING HARDWARE
- OIL-RUBBED BRONZE HW FINISH
- CUSTOM SILL CONFIGURATION
- HURRICANE GLAZING METHOD



Parrett's extensive experience with awning windows allowed us to create this unique unit to meet our customer's specific goals.

This awning unit was installed into a high-end residential "bartop" application and was designed to be without sill framing to provide a smooth, unobtrusive experience when the window is in the opened position.

As the awning sash is approx. 34 square feet, a unique piston operating hardware solution was employed that allowed this heavier sash to be quickly and easily operated.

Parrett also employed a glazing technique typically used in hurricane impact rated units, helping to ensure that this awning unit will remain stable and secure for the lifetime of the window.


Piston Awning Window Snapshot

Construction: Aluminum Clad
 Sash Thickness: 3-1/2"
 Factory Finishing: Exterior Factory Painted, Unfinished Ponderosa Pine Interior

PRESERVING AMERICA'S ARCHITECTURAL HERITAGE

Phone# 1-800-541-9527
 www.parrettwindows.com
 info@parrettwindows.com
 690 East Second Avenue, Dorchester, WI 54425





Piston Awning Specifications

Construction: Aluminum Clad Construction with Ponderosa Pine Interior

Frame Size: 96" W x 54" H

Sash Thickness: 3-1/2"

Jamb Depth: 4-9/16"

Sill: None (Customer Request)

Factory Finishing: Sherwin Williams Poly Paint (*Custom Color*)

Interior Finishing: Unfinished (Stain Grade)

Grilles: 7/8" Wide Horizontal and 2" Vertical SDL Bar Combination

Accessories: Aluminum Drip Cap, Vinyl Nailing Fin

Hardware: Piston Operated Hardware, Multipoint Locking Latch and (2) Pulls, Heavy Duty 4" Ball Bearing Hinges

DURABILITY, TRUE QUALITY, & SIMPLY BEAUTIFUL

EXPERIENCE THE DIFFERENCE!

*Temporary Sill Shown in Production Images Above